



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
CC-0301A	0.3-0.4	30	0.3	25	1.20	-15-+60	150	52*57.5*22	SMA/N
CC-0301S	0.3-0.4	30	0.6	50	1.20	-15-+60	150	104*57.5*22	SMA/N
CC-0401A	0.4-0.6	30	0.3	25	1.20	-15-+60	150	44*49.5*21	SMA/N
CC-0701A	0.4-0.6	10	0.3	23	1.20	-15-+60	150	35*38*20	SMA/N
	0.6-1.0	30				-30-+70			
CC-101	0.8-1.2	70	0.3	23	1.20	-30-+70	100	30*33*20	SMA/N
		200	0.5	20	1.25				
CC-101-S1	0.8-1.2	70	0.3	23	1.20	-30-+70	100	30*33*15	SMA
		200	0.5	20	1.25				
CC-101A	0.95-2.5	70	0.3	23	1.20	-30-+70	100	25.4*28.5*20	SMA/N
	1.0-2.5	200	0.4	20	1.25				
CC-101A-S1	0.95-2.5	70	0.3	23	1.20	-30-+70	100	25.4*28.5*15	SMA
	1.0-2.5	200	0.4	20	1.25				

Note: All the above data are obtained at room temperature.

### ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. [sales@eleadingchina.com](mailto:sales@eleadingchina.com)

[www.eleadingchina.com](http://www.eleadingchina.com)