



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
ID-102K	1.805-1.625	full	0.4	20	1.20	-30+70	10	15*16.5*6.6	TAB
ID-0902B1	1.5-2.0	70	0.3	23	1.20	-30+70	10	20*20*9	TAB
ID-0902B3	0.99-1.13	full	0.5	20	1.25	-30+70	10	20*20*9.1	TAB
ID-202D-E	1.4-2.4	70 200	0.3 0.4	25 20	1.20 1.25	-30+70	10	20*24.4*12	TAB
ID-202DS-E	1.7-1.9	70	0.6	45	1.20	-30+70	10	35*23.5*12	TAB
ID-202G-C1	1.7-2.5	30 100	0.3 0.3	25 23	1.20 1.20	-30+70	10	19*19*8.2	TAB
ID-202G-100	1.7-2.5	30 100	0.3 0.3	25 23	1.20 1.20	-30+70	100	19*27*8.2	TAB
ID-202H-5	1.7-2.8	70	0.3	22	1.20	-30+70	5	19*19*5.6	TAB
ID-202F-100	1.7-2.8	70	0.3	23	1.20	-30+70	100	19*25.4*5.6	TAB
ID-202FS-100	1.7-2.8	70	0.6	45	1.20	-30+70	100	38.1*25.4*5.6	TAB
ID-202H	1.7-2.3	100	0.3	23	1.20	-40+80	100	20*30*11.5	TAB
ID-202H2	2.2-2.3	full	0.5	20	1.25	-40+80	5	10*22.5*9.8	TAB
ID-202T1	2.2-2.8	100	0.4	20	1.20	-40+80	10	15*16.5*9.1	TAB

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com