


## Characteristics

- Wide Bandwidth
- Low Insertion
- High Isolation
- High Speed
- TTL Control



Notes: Frequency range, insertion loss, isolation, power rating and connection type, control mode and outline can be customized. And different application condition can also be customized.

## Specifications

Part Number	Frequency Range (GHz)	Insertion Loss (dB) max	Isolation (dB) min	VSWR max	Switch Speed (ns) max	Power Rating cw (w)	Outline
LT-CK42110	0.5—1.0	1.0	60	1.4	50	0.5	
LT-CK42120	1.0—2.0	1.2	60	1.4	50	0.5	
LT-CK32130	2.0—4.0	1.4	60	1.6	50	0.5	
LT-CK42140	4.0—8.0	1.8	60	1.8	50	0.5	
LT-CK42150	8.0—12.0	2.2	60	1.8	50	0.5	
LT-CK42160	12.0—18.0	2.8	60	2.0	50	0.5	
LT-CK42170	2.0—8.0	2.0	60	1.8	50	0.5	
LT-CK42180	8.0—18.0	2.8	60	2.0	50	0.5	
LT-CK42190	2.0—18.0	3.0	60	2.0	50	0.5	

## Application Notes

1. Power supply: Input from +V lead to +5V, current can be no more than 110mA ;From -V lead to -5V, current can only be up to 50mA ;
2. Control mode: When TTL input from Ei(i=1,2,3,4) and TTL is "0", voltage is now 0-0.8V, Ji(i=1,2,3,4)on ; When TTL is high as "1", voltage is 2-5.5V and Ji(i=1,2,3,4) is off.
3. Be sure if power supply is right connected and voltage can be no more than 20% of rated;

## Eleading Technologies Ltd.

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip 518081. Phn. ++86,755,2528 5648 Fax.2528

[eleading@vip.163.com](mailto:eleading@vip.163.com) [sales@eleadingchina.com](mailto:sales@eleadingchina.com) [www.eleavingchina.com](http://www.eleavingchina.com)